

4 Fast filtering algorithms

This exposition is based on

1. Flexible Pattern Matching in Strings, Navarro, Raffinot, 2002, chapter 6.5, pages 162ff.

We present the hierarchical filtering approach called *PEX* of Navarro and Baeza-Yates.

4.1 Filtering algorithms

The idea behind filtering algorithms is that it might be easier to check that a text position does *not* match a pattern string than to verify that it does.

Filtering algorithms *filter out* portions of the text that cannot possibly contain a match, leaving positions that could match.

The potential match positions then need to be *verified* with another algorithm like for example the bit-parallel algorithm of Myers (BPM).

Filtering algorithms are very sensitive to the *error level* $\alpha := k/m$ since this normally affects the amount of text that can be discarded from further consideration. (m = pattern length, k = errors.)

If most of the text has to be verified, the additional filtering steps are an overhead compared to the strategy of just verifying the pattern in the first place.

On the other hand, if large portions of the text can be discarded quickly, then the filtering results in a faster search.

Filtering algorithms can improve the average-case performance (sometimes dramatically), but not the worst-case performance.

Assume that we want to find all occurrences of a pattern $P = p_1, \dots, p_m$ in a text $T = t_1, \dots, t_n$ that have an edit distance of at most k .

If we *divide* the pattern into $k + 1$ pieces $P = p^1, \dots, p^{k+1}$, then at least *one* of the pattern pieces match *without error*.

There is a more general version of this principle first formalized by Myers in 1994:

Lemma 1. Let *Occ* match P with k errors, $P = p^1, \dots, p^j$ be a concatenation of subpatterns, and a_1, \dots, a_j be nonnegative integers such that $A = \sum_{i=1}^j a_i$. Then, for some $i \in 1, \dots, j$, *Occ* includes a substring that matches p^i with at most $\lfloor a_i k / A \rfloor$ errors.

Proof: *Exercise.*

So the basic procedure is:

1. *Divide:* Divide the pattern into $k + 1$ pieces of approximately the same length.
2. *Search:* Search all the pieces simultaneously with a multi-pattern string matching algorithm (or in a string index (BWT, ESA)). According to the above lemma, each possible occurrence will match at least one of the pattern pieces.
3. *Verify:* For each found pattern piece, check the neighborhood with a verification algorithm that is able to detect an occurrence of the whole pattern with edit distance at most k . Since we allow indels, if $p_{i_1} \dots p_{i_2}$ matches the text $t_j \dots t_{j+i_2-i_1}$, then the verification has to consider the text area $t_{j-(i_1-1)-k} \dots t_{j+(i_2-i_1)+k}$, which is of length $m + 2k$.

4.2 An example

Say we want to find the pattern *annual* in the texts

$t_1 = \text{any_annealing}$ and

$t_2 = \text{an_unusual_example_with_numerous_verifications}$

with at most 2 errors.

1. *Divide*: We divide the pattern *annual* into $p^1 = an$, $p^2 = nu$, and $p^3 = al$. One of these subpattern has to match with 0 errors.
2. *Search*: We search for all subpatterns:
 - 1: searching for *an*: in t_1 : find positions 1, 5
in t_2 : find position 1
 - 2: searching for *nu*: in t_1 : find no positions
in t_2 : find positions 5, 25
 - 3: searching for *al*: in t_1 : find position 9
in t_2 : find position 9
3. *Verification*: We have to verify 3 positions in t_1 , and 4 positions in t_2 , to find 3 occurrences in t_1 and *none* in t_2 .

4.3 Hierarchical verification

The toy example makes clear that *many* verifications can be triggered that are unsuccessful and that many subpatterns can trigger the *same* verification. Repeated verifications can be avoided by carefully sorting the occurrences of the pattern.

It was shown by Baeza-Yates and Navarro that the running time is dominated by the multipattern search for error levels $\alpha = k/m$ below $1/(3 \log_{|\Sigma|} m)$. In this region, the search cost is about $O(kn \frac{\log_{|\Sigma|} m}{m})$. For higher error levels, the cost for verifications starts to dominate, and the filter efficiency deteriorates abruptly.

Baeza-Yates and Navarro introduced the idea of hierarchical verification to reduce the verification costs, which we will explain next. Then we will work out more details of the three steps.

Navarro and Baeza-Yates use Lemma 1 for a *hierarchical verification*. The idea is that, since the verification cost is high, we pay too much for verifying the *whole* pattern *each* time a small piece matches. We could possibly reject the occurrence with a cheaper test for a shorter pattern.

So, instead of directly dividing the pattern into $k+1$ pieces, we do it hierarchically. We split the pattern first in two pieces and search for each piece with $\lfloor k/2 \rfloor$ errors, following Lemma 1. The halves are then recursively split and searched until the error rate reaches zero, i. e. we can search for exact matches.

With hierarchical verification, the area of applicability of the filtering algorithm grows to $\alpha < 1/\log_{|\Sigma|} m$, an error level three times as high as for the naive partitioning and verification. In practice, the filtering algorithm pays off for $\alpha < 1/3$ for medium long patterns.

Example. Say we want to find the pattern $P = aaabbbccddd$ in the text $T = xxxbbbxxxxxx$ with at most $k = 3$ differences. The pattern is split into four pieces $p^1 = aaa$, $p^2 = bbb$, $p^3 = ccc$, $p^4 = ddd$. We search with $k = 0$ errors in level 2 and find *bbb*.

level 0	aaabbbccddd	with k=3 errors
	/ \	
level 1	aaabbb cccddd	with k=1 errors
	/ \ / \	
level 2	aaa bbb ccc ddd	with k=0 errors

Now instead of verifying the complete pattern in the complete text (at level 0) with $k = 3$ errors, we only have to check a slightly bigger pattern (*aaabbb*) at level 1 with one error. This is much cheaper. In this example we can decide that the occurrence *bbb* cannot be extended to a match.

level 0	aaabbbccddd	with k=3 errors
	/ \	
level 1	AAABBB cccddd	with k=1 errors
	/ \ / \	
level 2	aaa BBB ccc ddd	with k=0 errors

4.4 The PEX algorithm

Divide: Split pattern into $k + 1$ pieces, such that each piece has equal probability of occurring in the text. If no other information is available, the uniform distribution is assumed and hence the pattern is divided in pieces of equal length.

Build Tree: Build a tree of the pattern for the hierarchical verification. If $k + 1$ is not a power of 2, we try to keep the binary tree as balanced as possible.

Each node has two members *from* and *to* indicating the first and the last position of the pattern piece represented by it. The member *err* holds the number of allowed errors. A pointer *myParent* leads to its parent in the tree. (There are no child pointers, since we traverse the tree only from the leafs to the root.) An internal variable *left* holds the number of pattern pieces in the left subtree. *idx* is the next leaf index to assign. *plen* is the length of a pattern piece.


Algorithm CreateTree generates a hierarchical verification tree for a single pattern. (Lines 12 and 14 are justified by Lemma 1.)

```

(1) CreateTree( $p = p_i p_{i+1} \dots p_j, k, myParent, idx, plen$ )
(2) // Note: the initial call is: CreateTree( $p, k, nil, 0, \lfloor m/(k+1) \rfloor$ )
(3) Create new node  $node$ 
(4)  $from(node) = i$ 
(5)  $to(node) = j$ 
(6)  $left = \lceil (k+1)/2 \rceil$ 
(7)  $parent(node) = myParent$ 
(8)  $err(node) = k$ 
(9) if  $k = 0$ 
(10) then  $leaf_{idx} = node$ 
(11) else
(12)    $lk = \lfloor (left \cdot k)/(k+1) \rfloor$ 
(13)   CreateTree( $p_i \dots p_{i+left-plen-1}, lk, node, idx, plen$ )
(14)    $rk = \lfloor ((k+1-left) \cdot k)/(k+1) \rfloor$ 
(15)   CreateTree( $p_{i+left-plen} \dots p_j, rk, node, idx+left, plen$ )
(16) fi

```

Example: Find the pattern $P = \text{annual}$ in the text $T = \text{annual.CPM.anniversary}$ with at most $k = 2$ errors. First we build the tree with $k + 1 = 3$ leaves. Below we write at each node n_i the variables (*from, to, error*).



Search: After constructing the tree, we have $k + 1$ leafs $leaf_i$. The $k + 1$ subpatterns

$$\{ p_{from(n)}, \dots, p_{to(n)}, n = leaf_i, i \in \{0, \dots, k\} \}$$

are sent as input to a multi-pattern search algorithm (e. g. Aho-Corasick, Wu-Manbers, or SBOM). This algorithm gives as output a list of pairs (pos, i) where pos is the text position that matched and i is the number of the piece that matched.

The PEX algorithm performs verifications on its way upward in the tree, checking the presence of longer and longer pieces of the pattern, as specified by the nodes.

```

(1) Search phase of algorithm PEX
(2) for  $(pos, i) \in$  output of multi-pattern search do
(3)    $n = leaf_i; in = from(n); n = parent(n);$ 
(4)    $cand = true;$ 

```

```

(5)  while cand = true and n ≠ nil do
(6)      p1 = pos - (in - from(n)) - err(n);
(7)      p2 = pos + (to(n) - in) + err(n);
(8)      verify text tp1 ... tp2 for pattern piece pfrom(n) ... pto(n)
(9)      allowing err(n) errors;
(10)     if pattern piece was not found
(11)         then cand = false;
(12)         else n = parent(n);
(13)     fi
(14) od
(15) if cand = true
(16)     then report the positions where the whole p was found;
(17) fi
(18) od

```

We search for `annual` in `annual.CPM.anniversary`. We constructed the tree for `annual`. A multi-pattern search algorithm finds: (1,1), (12,1), (3,2), (5,3). (Note that leaf i corresponds to pattern p^{i+1}). For each of these positions we do the hierarchical verification:

```

Initialization for (1,1);
n=n0; in=1; n=n3; cand=true;
While loop;
  a) p1=1-(1-1)-1=0; p2=1+(4-1)+1=5;
  verify pattern annu in text annua with 1 error => found !
  b) p1=1-(1-1)-2=-1; p2=1+(6-1)+2=8;
  verify pattern annual in text annual_C => found !
  c) report end positions (6,7,8)

```

```

Initialization for (3,2);
n=n1; in=3; n=n3; cand=true;
While loop;
  a) p1=3-(3-1)-1=0; p2=3+(4-3)+1=5;
  verify pattern annu in text annua with 1 error => found !
  b) p1=3-(3-1)-2=-1; p2=3+(6-3)+2=8;
  verify pattern annual in text annual_C => found !
  c) report end positions (6,7,8)

```

```

Initialization for (12,1);
n=n0; in=1; n=n3; cand=true;
While loop;
  a) p1=12-(1-1)-1=11; p2=12+(4-1)+1=16;
  verify pattern annu in text _anniv with 1 error => found !
  b) p1=12-(1-1)-2=10; p2=12+(6-1)+2=19;
  verify pattern annual in text M_annivers => NOT found !

```

Note that sorting of the leaf matches would avoid verifying the match three times.

4.5 Summary

- Filtering algorithms prevent a large portion of the text from being looked at.
- The larger $\alpha = k/m$, the less efficient filtering algorithms become.
- Filtering algorithms based on the pigeonhole principle need an exact, multi-pattern search algorithm and a verification capable approximate string matching algorithm.
- The PEX algorithm starts verification from short exact matches and considers longer and longer substrings of the pattern as the verification proceeds upward in the tree.